

QFA-3 Quilted Fiberglass Absorber

Sound Seal QFA-3 quilted fiberglass absorber blanket offers excellent sound absorption. It is comprised of a single layer of 1" fiberglass batting quilted with a non-woven porous scrim fabric on both sides. Full locking stitches are available in a diamond or straight stitch pattern. Standard roll size is 4' wide up to 50' long. Also available 54" wide.

- Class A Flammability Rated per ASTM E-84
- NRC rating 0.70
- 1" thick, scrim faced both sides

Applications:

Typically used as a sound absorption panel or an acoustical liner. Also used as a decoupler when combined with our B-10 Lag Acoustical Pipe & Duct product to enhance its acoustical performance.

Product Data:

Description	non-woven porous scrim /fiberglass batt/ non-woven porous scrim
Nominal thickness	1.0"
Temperature range	-20° to +350° F
Standard width	48"
Roll length	50'
Density	1.6 lb/ft ³
Flammability	Flame Spread: 5.07 Smoke Density: .45

Acoustical Performance:

Sound Absorption Data

Product	OCTAVE BAND FREQUENCIES (Hz)						NRC
	125	250	500	1000	2000	4000	
QFA-3	.28	.24	.62	.91	.98	1.01	.70

Per ASTM C 423